In accordance to Annex III of Regulation (EU) Nr. 305/2011



LE-H01030-03

BARUSIN RP 350/21



Purpose

· Basement waterproofing systems against soil moisture

Name, contact producer

BÜSSCHER & HOFFMANN GmbH A-4

A-4470 (AT) Fabrikstraße 2 Tel.: +43 (7223) 823 23-0 Web: www.bueho.com E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system2+	EN 13969:2004 + A1:2006
Harmonized standard	EN 13969:2004 + A1:2006
Notified body	1139 WIEN-ZERT Rinnböckstraße 15, A-1110 Wien
Certificate of conformity	1139-CPR-0027/06

Declared performance

		Harmonized technical
Essential characteristics	Performance	specification
Watertightness	10 kPa	EN 13969:2004 + A1:2006
Reaction to fire test	Е	EN 13969:2004 + A1:2006
Shear resistance of joints	NPD	EN 13969:2004 + A1:2006
Tensile force long./trans.	350/250 (±100/±100) N/50mm	EN 13969:2004 + A1:2006
Elongation at single-end breaking force	1,5/1,5 (±1/±1) %	EN 13969:2004 + A1:2006
Resistance to impact	NPD	EN 13969:2004 + A1:2006
Resistance to static loading	NPD	EN 13969:2004 + A1:2006
Resistance to tearing (nail shank) long./trans.	80/80 (±25/±25) N	EN 13969:2004 + A1:2006
Flexibility at low temperatures	0 °C	EN 13969:2004 + A1:2006
Watertightness transmission after artifical aging	10 kPa	EN 13969:2004 + A1:2006
Watertightness after exposure to liquid chemicals	NPD	EN 13969:2004 + A1:2006
Hazardous substances	None	EN 13969:2004 + A1:2006

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by

land Loudt

Bmstr. Dipl. Ing. Karl Landl

General Manager

Issue date: 2024.01.14 Page 1 / 1

[[]a] This declaration of performance is available in copy at the website of the producer

[[]b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.